

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

VETRI

## TECHNICAL CHARACTERISTICS

Available Formats:	24X24, 12X24, 8X24, 4X12		
Style Description:	Glass Look	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Shiny smooth plain color	Number of Faces/Screens:	1
Thickness in mm:	9mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy Polished
Rectified:	Yes	Recommended Grout Joint:	2 mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	Complaint
Frost Resistant:	Yes	Thermal Shock Resistance:	Complaint
PEI/Abrasion Resistance:	IV+	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Compliant		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.56	Pieces per Carton:	7
SqFt per Pallet:	542.40	Pounds per Carton:	
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:			

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*