

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

Woodville

## TECHNICAL CHARACTERISTICS

Available Formats:	6x36 Floor		
Style Description:	Wood	Glaze Application Method:	H.D.I.T. Rectified Products
Visual Characteristics:	Real Wood Appearance	Number of Faces/Screens:	6
Thickness in mm:	9 mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential / Commercial	Color Body Unglazed:	White
Recycled Content: Post or Pre Customer	5	Surface Type:	Matte
Rectified:	Pressed	Recommended Grout Joint:	2 mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	3	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	Minimum 3	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:	Fullfill		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.08	Pieces per Carton:	9
SqFt per Pallet:	627.84	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	22		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*