

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

Yosemite

## TECHNICAL CHARACTERISTICS

Available Formats:	36x36, 24x24, 12x24, 3x24 Bullnose		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Limestone	Number of Faces/Screens:	36x36:16, 24x24: 32, 12x24: 64
Thickness in mm:	11 (cm90x90) - 10mm (CM60x60- cm30x60)	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Colored
Recycled Content: Post or Pre Customer	40%	Surface Type:	Matte, Flat
Rectified:	Yes	Recommended Grout Joint:	3/16"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	7.5	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	V2	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	17.44	Pieces per Carton:	2
SqFt per Pallet:	523.20	Pounds per Carton:	
Boxes per Pallet:		SqFt per Container:	
Pallets per Container:	17		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*