

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Zera Annex

TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose.		
Style Description:	Fabric	Glaze Application Method:	
Visual Characteristics:		Number of Faces/Screens:	8
Thickness in mm:	10	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	Yes	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	≤0.1%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	≥0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	≥600
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Class A		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	16	Pieces per Carton:	8
SqFt per Pallet:	448.00	Pounds per Carton:	71.68
Boxes per Pallet:	28	SqFt per Container:	12544.00
Pallets per Container:	28		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.