

NEW PRODUCT SERIES

Technical Information Spec-sheet



INTERNATIONAL WHOLESALE TILE, LLC

SERIES NAME

DISTRICT 6x6

TECHNICAL CHARACTERISTICS

Available Formats:	6x6		
Style Description:	Contemporary	Glaze Application Method:	Ink Jet
Thickness in mm:	10	Number of Faces/Screens:	1
Application:	Floor / Wall / Pool	Number of Punches/Molds:	1
Rectified or Pressed:	Pressed	Body Type:	Color Body Porcelain
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Matt
		Recommended Grout Joint:	3/16

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< 0.5%	Chemical Resistance:	Yes
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	> 0.42
Frost Resistant:	Yes	Breaking Strength:	> 1600 N
PEI/Abrasion Resistance:		Thermal Shock Resistance:	Yes

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.