

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Scavo II

TECHNICAL CHARACTERISTICS

Available Formats:	6x6		
Style Description:	Stone	Glaze Application Method:	Inkjet
Visual Characteristics:	Stone	Number of Faces/Screens:	7
Thickness in mm:	8.1 mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified or Pressed	Pressed	Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.05%	Static COF:	N/A
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	6	Breaking Strength:	<1300 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	5	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Pool Rated		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.