

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**Terra Bella Silver Astek**

## TECHNICAL CHARACTERISTICS

Available Formats:	15.75x11.75		
Style Description:		Glaze Application Method:	
Visual Characteristics:		Number of Faces/Screens:	
Thickness in mm:	10mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	
Application:	Residential Wall/Floor Exterior Wall	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glass
Rectified or Pressed		Recommended Grout Joint:	2 MM

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	E<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)		Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Resistant	Thermal Shock Resistance:	+15/+17 Celsius
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Resistant		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".