

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

ONYX

TECHNICAL CHARACTERISTICS

Available Formats:	6x6 Field Tile		
Style Description:	Decorative	Glaze Application Method:	Inkjet
Visual Characteristics:	Glossy	Number of Faces/Screens:	1
Thickness in mm:	8.5	Number of Punches/Molds:	1
Modular Suitability:	N/A	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Smooth / Glossy
Rectified or Pressed	Pressed	Recommended Grout Joint:	3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0.40
Scratch Hardness (MOHS)	5	Breaking Strength:	Complies
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	2	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	A		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.