

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**Carrara Ultra White Gloss**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24		
Style Description:	Carrara Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	14
Thickness in mm:	7.5 MM	Number of Punches/Molds:	1
Modular Suitability:		Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy
Rectified:	No	Recommended Grout Joint:	2MM   0.08

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	.20 wet
Scratch Hardness (MOHS)	5	Breaking Strength:	Meets
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	>GLB		

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	17.44	Pieces per Carton:	9
SqFt per Pallet:	837.12	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	16		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*