

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**FUORITONO**

## TECHNICAL CHARACTERISTICS

Available Formats:	4X12, Hexagon, Rhomboid		
Style Description:	Hand Glazed and Fired Tile	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	4x12-30/ Rhomboid-34/ Hex-16
Thickness in mm:	10.0mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	20%	Surface Type:	Glossy/Textured
Rectified:	No	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.30%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4- V5 Bianco only	Dynamic COF:	<0.42
Scratch Hardness (MOHS)	>5	Breaking Strength:	>400 LBF
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Class A		

## PACKING INFORMATION - 4x12 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	5.49	Pieces per Carton:	17
SqFt per Pallet:	527.04	Pounds per Carton:	
Boxes per Pallet:	96	SqFt per Container:	
Pallets per Container:			

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".