

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**MARBELA**

## TECHNICAL CHARACTERISTICS

Available Formats:	20x20		
Style Description:	Matte	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	8
Thickness in mm:	9.8-10.1mm	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Flat
Rectified:	Yes	Recommended Grout Joint:	2 mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.5% or less	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	<0.4
Scratch Hardness (MOHS)		Breaking Strength:	1200N
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:			

## PACKING INFORMATION - 20x20 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	16.15	Pieces per Carton:	6
SqFt per Pallet:	904.40	Pounds per Carton:	
Boxes per Pallet:	56	SqFt per Container:	
Pallets per Container:	15		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".