

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**SHELLSTONE**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 24x24, 24x48, 4x12,		
Style Description:	Shellstone Look	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	8 (24x48), 16 (24x24)
Thickness in mm:	9.5 mm (12x24,24x24,4x12) 10mm (24x48)	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	>30%	Surface Type:	Matte/Flat
Rectified:	Yes	Recommended Grout Joint:	2 mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	0.10%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0.42 Outdoor .74
Scratch Hardness (MOHS)		Breaking Strength:	>40 N/mm <sup>2</sup>
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	Amber (4), White (5), Grey (4)	Deep Abrasion Test <175mm <sup>2</sup> :	Yes
Chemical Resistance:			

## PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.63	Pieces per Carton:	6
SqFt per Pallet:	558.24	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	22		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*