

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

NAME	SERIES	Soho
------	--------	------

TECHNICAL CHARACTERISTICS			
Available Formats:	8x24, 8x16, 4x12, 4x16, 6x6*, 2x12, 3x6 2x8BN, 2x6BN, 12"QR		
Style Description:	Flat	Glaze Application Method:	Waterfall
Visual Characteristics:	Subway Tile	Number of Faces/Screens:	N/A
Thickness in mm:	7-9mm depending on size	Number of Punches/Molds:	N/A
Modular Suitability:	Yes	Body Type:	Ceramic
Application:	-Residential Wall -Commercial Wall	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	Gloss & Matte White
Rectified:	No	Recommended Grout Joint:	N/A

*White Glossy Only

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	10-18%	Static COF:	N/A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	N/A
Scratch Hardness (MOHS)	2	Breaking Strength:	>1000N
Frost Resistant:	No	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	N/A	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	Class B		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

NAME	SERIES	Soho Mosaics
------	--------	--------------

TECHNICAL CHARACTERISTICS			
Available Formats:	0.75 Penny Round Glossy/Matte, 1" Hex Matte, 1" Hex w/Insert Matte, 2" Hex Matte, 2x2 Square Matte, Basketweave w/Insert Matte, 2x5 Picket Glossy/Matte, 2x6 Glossy/Matte, 2x6 Herringbone Glossy/Matte, Scallop Glossy, Beveled Arabesque Glossy		
Style Description:	Solid color mosaic Mosaic with insert	Glaze Application Method:	Rotocolor
Visual Characteristics:	Mosaic	Number of Faces/Screens:	N/A
Thickness in mm:	6mm 7mm Bevel Arabesque	Number of Punches/Molds:	N/A
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	-Residential Wall -Commercial Wall -Residential Floor*	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	N/A	Surface Type:	-Gloss & Matte -Relief (Arabesque and Scallop only)
Rectified:	No	Recommended Grout Joint:	N/A

*Arabesque and Scallop wall only

PRODUCT TESTING INFORMATION			
<i>Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)</i>			
Water Absorption:	<.5%	Static COF:	N/A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>.42 Glossy, Matte
Scratch Hardness (MOHS)	5 Glossy 6 Matte	Breaking Strength:	>1220N
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	-0 Arabesque, Scallop -3 Glossy -4 Matte	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	Class A		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Soho Blended Mosaic

TECHNICAL CHARACTERISTICS

Available Formats:	Plaid Pattern, Cubic Pattern, Chain Pattern, Hexagon Pattern, Diamond Pattern		
Style Description:	Pattern Mosaic	Glaze Application Method:	Standard Screen
Thickness in mm:	6 mm	Number of Faces/Screens:	N/A
Application:	-Residential Wall -Commercial Wall -Exterior Wall -Residential Floor	Number of Punches/Molds:	N/A
Rectified or Pressed:	Pressed	Body Type:	Porcelain
Recycled Content:	10% Pre	Surface Type:	Matte
		Recommended Grout Joint:	1/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5	Chemical Resistance:	CLASS A
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	≥0.42
Frost Resistant:	YES	Breaking Strength:	ANSI >275 / ISO >1220
PEI/Abrasion Resistance:	4	Thermal Shock Resistance:	N/A

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.