

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**Bioko**

## TECHNICAL CHARACTERISTICS

Available Formats:	18x18		
Style Description:	marble	Glaze Application Method:	
Visual Characteristics:	Fume or Subway	Number of Faces/Screens:	12
Thickness in mm:		Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	4%	Surface Type:	
Rectified:	No	Recommended Grout Joint:	3 mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	>0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.4
Scratch Hardness (MOHS)	4	Breaking Strength:	>600N
Frost Resistant:	No	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	26.16	Pieces per Carton:	11
SqFt per Pallet:	1464.96	Pounds per Carton:	
Boxes per Pallet:	56	SqFt per Container:	
Pallets per Container:	14		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*