NEW PRODUCT SERIES

Technical Information Spec-sheet





SERIES NAME

BOTANIC

TECHNICAL CHARACTERISTICS					
Available Formats:	11X46.5				
Style Description:	Wood	Glaze Application Method:	Inkjet		
Visual Characteristics:		Number of Faces/Screens:	8		
Thickness in mm:	9.5-10.0mm	Number of Punches/Molds:	1		
Modular Suitability:		Body Type:	Ceramic		
Application:	Residential/Commercial	Color Body Unglazed:	Red Body		
Recycled Content:		Surface Type:	Flat, Matte		
Post or Pre Customer					
Rectified:	Yes	Recommended Grout Joint:			

PRODUCT TESTING INFORMATION						
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)						
Water Absorption:	<0.4%	Static COF:				
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	<0.4			
Scratch Hardness (MOHS)		Breaking Strength:	1200n			
Frost Resistant:	No	Thermal Shock Resistance:				
PEI/Abrasion Resistance:	4	Deep Abrasion Test				
		<175mm ² :				
Chemical Resistance:	GB & GLB		•			

PACKING INFORMATION - 3x8 Please inquire with Customer Service for additional sizes					
SqFt per Carton:	18.19	Pieces per Carton:	5		
SqFt per Pallet:	582.08	Pounds per Carton:			
Boxes per Pallet:	32	SqFt per Container:			
Pallets per Container:	24				

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4% to 3/16% but no less than 1/8%.