

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

ETNA WOOD

TECHNICAL CHARACTERISTICS

Available Formats:	9X35.5		
Style Description:	Wood Plank	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	15
Thickness in mm:	9	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Sand White
Recycled Content: Post or Pre Customer	4%	Surface Type:	Matte/Flat
Rectified:	Yes	Recommended Grout Joint:	2 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	5	Breaking Strength:	>1500
Frost Resistant:	Yes	Thermal Shock Resistance:	Yes
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	>GB		

PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	19.59	Pieces per Carton:	9
SqFt per Pallet:	940.32	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	16		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.