

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**GLEEZE**

## TECHNICAL CHARACTERISTICS

Available Formats:	2X6, 3X8, 4X4		
Style Description:	Fume	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	40
Thickness in mm:		Number of Punches/Molds:	1
Modular Suitability:		Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy
Rectified:	No	Recommended Grout Joint:	

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	<u>Not Rated</u>
Scratch Hardness (MOHS)		Breaking Strength:	>1300
Frost Resistant:	Yes	Thermal Shock Resistance:	Complies
PEI/Abrasion Resistance:	4 (Decos Not rated)	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	GB		

## PACKING INFORMATION - 3x8 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	8.07	Pieces per Carton:	50
SqFt per Pallet:	613.32	Pounds per Carton:	
Boxes per Pallet:	76	SqFt per Container:	
Pallets per Container:	19		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".