

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Laminus

TECHNICAL CHARACTERISTICS

Available Formats:	11x46.5		
Style Description:	Wood Plank	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	16
Thickness in mm:	9.5-10.0	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Flat
Rectified:	Yes	Recommended Grout Joint:	3-4,5 mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.5% to 7%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	<.40
Scratch Hardness (MOHS)		Breaking Strength:	1200N
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4 (Marfil & Palha) 3 (Brown)	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	GB & GLB		

PACKING INFORMATION - 11x46.5 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	18.19	Pieces per Carton:	5
SqFt per Pallet:	582.08	Pounds per Carton:	
Boxes per Pallet:	32	SqFt per Container:	
Pallets per Container:	24		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".