

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

Oceania

TECHNICAL CHARACTERISTICS

Available Formats:	18x18, 14x14		
Style Description:		Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:	Stone Look	Number of Faces/Screens:	18x18(4), 14x14(6)
Thickness in mm:	6.9mm / 6.8mm	Number of Punches/Molds:	Flat punch
Modular Suitability:	No	Body Type:	Ceramic
Application:	Residential	Color Body Unglazed:	red
Recycled Content: Post or Pre Customer	No	Surface Type:	Matte and Flat
Rectified:	No	Recommended Grout Joint:	4mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	6%	Static COF:	
Shade Variation (1, 2, 3, 4)	2	Dynamic COF:	<.42
Scratch Hardness (MOHS)		Breaking Strength:	20N/nm ²
Frost Resistant:	No	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

PACKING INFORMATION - 18x18 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	27.77	Pieces per Carton:	12
SqFt per Pallet:	1221.88	Pounds per Carton:	
Boxes per Pallet:	44	SqFt per Container:	
Pallets per Container:	18		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".