

# NEW PRODUCT SERIES

Technical Information Spec-sheet



**International  
Wholesale  
Tile, LLC**

SERIES NAME

Scavo

## TECHNICAL CHARACTERISTICS

Available Formats:	18x18, 12x24, 12x12, 6x6, 3x6, 3x12 Floor Bullnose and 2x2 Mosaic 12x12 Sheet		
Style Description:	Traditional stone	Glaze Application Method:	H.D.I.T Inkjet
Visual Characteristics:	Travertine	Number of Faces/Screens:	16
Thickness in mm:		Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Gres Porcelain
Application:	Residential	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	3/16"

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:		Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.49
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	15.29	Pieces per Carton:	7
SqFt per Pallet:	795.08	Pounds per Carton:	3421.45
Boxes per Pallet:	52	SqFt per Container:	10,336.04
Pallets per Container:	13		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".