

NEW PRODUCT SERIES

Technical Information Spec-sheet



**International
Wholesale
Tile, LLC**

SERIES NAME

Travel

TECHNICAL CHARACTERISTICS

Available Formats:	18x36, 12x24, 2x2 Mosaic 12x12 Sheet, 3x24 Bullnose		
Style Description:	Vein Cut Marble	Glaze Application Method:	H.D.I.T. Inkjet
Visual Characteristics:		Number of Faces/Screens:	24
Thickness in mm:	9mm(12x24), 10mm(18x36)	Number of Punches/Molds:	4
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Yes
Recycled Content: Post or Pre Customer	40%	Surface Type:	
Rectified:	18x36 Rectified	Recommended Grout Joint:	3mm(12x24), 4mm(18x36)

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.05%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	7	Breaking Strength:	600 lbf
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	V	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	A Resistant		

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	13.13	Pieces per Carton:	3
SqFt per Pallet:	367.64	Pounds per Carton:	59.611
Boxes per Pallet:	28	SqFt per Container:	9558.64
Pallets per Container:	26		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".