

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

V-STONE

TECHNICAL CHARACTERISTICS

Available Formats:	19x38 (Matte Only), 9x38 (Matte Only), 19x19, 19x19 Cross, 2x2 Mosaic 12x12 Sheet, 1.5x1.5 Mosaic 12x12 Sheet, 3x19 Bullnose		
Style Description:	Matte & Semi-Polished	Glaze Application Method:	HDIT Inkjet
Visual Characteristics:	Marble Blend	Number of Faces/Screens:	6 Sq meters
Thickness in mm:	10mm	Number of Punches/Molds:	3
Modular Suitability:	No	Body Type:	Porcelain (< .5%)
Application:	Residential/Commercial	Color Body Unglazed:	No
Recycled Content: Post or Pre Customer	No	Surface Type:	Matte
Rectified:	No	Recommended Grout Joint:	No less than 3/16"

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	< .5%	Static COF:	Wet: .42 Dry: 0.42
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	N/A
Scratch Hardness (MOHS)	N/A	Breaking Strength:	ISO 10545.5 Conforms
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	IV	Deep Abrasion Test <175mm ² :	N/A
Chemical Resistance:	ISO 10545.13-A		

PACKING INFORMATION - 19x19 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	14.75	Pieces per Carton:	6
SqFt per Pallet:	354.00	Pounds per SqFt:	4.50 Lbs
Boxes per Pallet:	24	SqFt per Container:	N/A
Pallets per Container:	N/A		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.