

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Cortina

TECHNICAL CHARACTERISTICS

Available Formats:	6x36, 10x60		
Style Description:		Glaze Application Method:	Inkjet
Visual Characteristics:	Wood Effect	Number of Faces/Screens:	30
Thickness in mm:	9mm/20mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	Tobacco >20%	Surface Type:	Matte Textured
Rectified:	Yes	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.2%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	>0.42
Scratch Hardness (MOHS)		Breaking Strength:	>35 N/mm ²
Frost Resistant:	Yes	Thermal Shock Resistance:	Compliant
PEI/Abrasion Resistance:	5	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:			

PACKING INFORMATION - 6x36 Please inquire with Customer Service for additional sizes

SqFt per Carton:	14.53	Pieces per Carton:	10
SqFt per Pallet:	523.08	Pounds per Carton:	
Boxes per Pallet:	36.00	SqFt per Container:	
Pallets per Container:	26.00		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".