

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Majestic

TECHNICAL CHARACTERISTICS

Available Formats:	12x24 Glossy		
Style Description:	Marble	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	17
Thickness in mm:	9.8 MM	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Gres Porcelain
Application:	Residential	Color Body Unglazed:	White
Recycled Content: Post or Pre Customer	39%	Surface Type:	Glossy/Polished
Rectified:	Yes	Recommended Grout Joint:	1.5 MM-3MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	No
Scratch Hardness (MOHS)	5	Breaking Strength:	1500 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Compliant
PEI/Abrasion Resistance:	12x24: 3 13x26: 4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:			

PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt per Carton:	11.36	Pieces per Carton:	6
SqFt per Pallet:	454.40	Pounds per Carton:	
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:	26		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".