

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

DELRAY II

TECHNICAL CHARACTERISTICS

Available Formats:	28x28		
Style Description:	Marble	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	12x24: 20, 28x28: 10
Thickness in mm:	8.5 MM	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	5%	Surface Type:	
Rectified:	Rectified	Recommended Grout Joint:	5 MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	Polished: N/A Matte: 0.42
Scratch Hardness (MOHS)	6 for Polished and 7 for Matte	Breaking Strength:	PASS
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:	Resistant		

PACKING INFORMATION - 28x28 *Please inquire with Customer Service for additional sizes*

		Pieces per Carton:	4
SqFt per Pallet:	861.20	Pounds per Carton:	
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:	18		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".