

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

OLIMPO

TECHNICAL CHARACTERISTICS

Available Formats:	12x24 and 28x28		
Style Description:	Marble	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	28x28 (15), 12x24 (30)
Thickness in mm:	8.5 MM	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer	5%	Surface Type:	
Rectified:	Rectified	Recommended Grout Joint:	5MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	Polished- N/A Matte: 0.42
Scratch Hardness (MOHS)	6 for Polished and 7 for Matte	Breaking Strength:	Greater than 250 LBF
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

		Pieces per Carton:	8
SqFt per Pallet:	839.60	Pounds per Carton:	
Boxes per Pallet:	40	SqFt per Container:	
Pallets per Container:	27		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.