

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ABADIA**

## TECHNICAL CHARACTERISTICS

Available Formats:	Hexagon		
Style Description:	Cotto	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	31
Thickness in mm:	10 MM	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	Pressed	Recommended Grout Joint:	2mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	Less than 0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	>.42
Scratch Hardness (MOHS)	6	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm <sup>2</sup> :	n0
Chemical Resistance:	GA-GHA-GLA		

## PACKING INFORMATION - 6x36 *Please inquire with Customer Service for additional sizes*

SqFt. Per Carton	11.20	Pieces per Carton:	25
SqFt per Pallet:	582.40	Pounds per Carton:	
Boxes per Pallet:	52	SqFt per Container:	
Pallets per Container:	16		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".