

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**BAY**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24		
Style Description:	Marble	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	8
Thickness in mm:	9.2 MM	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	
Rectified:	Rectified	Recommended Grout Joint:	2 MM

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<05 Max	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	n/a
Scratch Hardness (MOHS)	7	Breaking Strength:	Pass
Frost Resistant:	Yes	Thermal Shock Resistance:	n/a
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:			

## PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

		Pieces per Carton:	
SqFt per Pallet:		Pounds per Carton:	
Boxes per Pallet:		SqFt per Container:	
Pallets per Container:			

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".