

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

BAY

TECHNICAL CHARACTERISTICS

Available Formats:	24x24		
Style Description:	Marble	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	8
Thickness in mm:	9.2 mm	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Commercial	Color Body Unglazed:	Off White
Recycled Content: Post or Pre Customer	3%	Surface Type:	Matte/Flat
Rectified:	Rectified	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<=0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	
Scratch Hardness (MOHS)	7	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Pass		

PACKING INFORMATION - 2x10 *Please inquire with Customer Service for additional sizes*

SqFt. Per Carton	15.50	Pieces per Carton:	4
SqFt per Pallet:	558.00	Pounds per Carton:	
Boxes per Pallet:	36.00	SqFt per Container:	
Pallets per Container:	26		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.