

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

LEXINGTON

TECHNICAL CHARACTERISTICS

Available Formats:	6x36		
Style Description:	Wood Plank	Glaze Application Method:	Inkjet
Visual Characteristics:	Modern wood	Number of Faces/Screens:	9
Thickness in mm:	9 MM	Number of Punches/Molds:	1-Flat
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	Pressed	Recommended Grout Joint:	3 MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.4	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	0.63
Scratch Hardness (MOHS)	7	Breaking Strength:	450
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	Yes		

PACKING INFORMATION - 6x36 *Please inquire with Customer Service for additional sizes*

SF per Ct	11.63	Pieces per Carton:	8
SqFt per Pallet:	488.46	Pounds per Carton:	
Boxes per Pallet:	42	SqFt per Container:	
Pallets per Container:	30		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.