

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**PROVENCA**

## TECHNICAL CHARACTERISTICS

|   |             |                           |                     |
|---|-------------|---------------------------|---------------------|
| Available Formats:                        | 24x24       |                           |                     |
| Style Description:                        | Satin Style | Glaze Application Method: | Inkjet              |
| Visual Characteristics:                   | Terracotta  | Number of Faces/Screens:  | 8                   |
| Thickness in mm:                          | 9.2 mm      | Number of Punches/Molds:  | 1                   |
| Modular Suitability:                      | Yes         | Body Type:                | Porcelain           |
| Application:                              | Commercial  | Color Body Unglazed:      | Off White           |
| Recycled Content:<br>Post or Pre Customer | 3%          | Surface Type:             | Matte/Flat/Textured |
| Rectified:                                | Rectified   | Recommended Grout Joint:  | 2 MM                |

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

|                              |                           |   |     |
|------------------------------|---------------------------|---|-----|
| Water Absorption:            | Eb <= 0.5% Máx. ind. 0.6% | Static COF:                                 |     |
| Shade Variation (1, 2, 3, 4) | V3                        | Dynamic COF:                                | N/A |
| Scratch Hardness (MOHS)      | 7                         | Breaking Strength:                          |     |
| Frost Resistant:             | Yes                       | Thermal Shock Resistance:                   | N/A |
| PEI/Abrasion Resistance:     | 4                         | Deep Abrasion Test<br><175mm <sup>2</sup> : | No  |
| Chemical Resistance:         | Pass                      |   |     |

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*