

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ALTEA**

## TECHNICAL CHARACTERISTICS

Available Formats:	3x6, 4x4		
Style Description:	White Body Ceramic	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	
Thickness in mm:	9 MM	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy/Textured
Rectified:	Pressed	Recommended Grout Joint:	>2 MM

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	>10%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)	3	Breaking Strength:	PASS
Frost Resistant:		Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	Yes		

## PACKING INFORMATION - 3x6 *Please inquire with Customer Service for additional sizes*

		Pieces per Carton:	44
SqFt per Pallet:	645.60	Pounds per Carton:	
Boxes per Pallet:	120	SqFt per Container:	
Pallets per Container:	22		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".