

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

LANSE

TECHNICAL CHARACTERISTICS

Available Formats:	2x10 Picket		
Style Description:	White Body Ceramic	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	
Thickness in mm:	9 MM	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Textured
Rectified:	Pressed	Recommended Grout Joint:	>2 MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	>10%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	
Scratch Hardness (MOHS)	3	Breaking Strength:	>600
Frost Resistant:		Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Yes		

PACKING INFORMATION - 2x10 *Please inquire with Customer Service for additional sizes*

		Pieces per Carton:	44
SqFt per Pallet:	645.60	Pounds per Carton:	
Boxes per Pallet:	120	SqFt per Container:	
Pallets per Container:	22		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.