

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**PAONAZZO**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24, 24x24, 36x36		
Style Description:	Calacatta Gold	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	12x24(38), 24x24(26), 36x36 (10)
Thickness in mm:	10.5 MM	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Glossy
Rectified:	Rectified	Recommended Grout Joint:	2.5mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	Matte 0.42
Scratch Hardness (MOHS)		Breaking Strength:	1600-2400N
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

## PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt. Per Carton	11.63	Pieces per Carton:	6
SqFt per Pallet:	558.24	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	25		

### Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".