

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

ADVANCE

TECHNICAL CHARACTERISTICS

Available Formats:	12x24/ 24X24/ 36X36		
Style Description:	Stone Look	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	12x24(48), 24x24(24), 36x36 (12)
Thickness in mm:	9 MM	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Glossy
Rectified:	Rectified	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>.42 (Dry)
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Resistant		

PACKING INFORMATION - 12x24 *Please inquire with Customer Service for additional sizes*

SqFt. Per Carton	17.44	Pieces per Carton:	9
SqFt per Pallet:	558.08	Pounds per Carton:	
Boxes per Pallet:	32	SqFt per Container:	
Pallets per Container:	20		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".