

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

NINSBA

TECHNICAL CHARACTERISTICS

Available Formats:	6x36		
Style Description:	Wood	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	19
Thickness in mm:	9 MM	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified:	Pressed	Recommended Grout Joint:	3mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.10%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.53
Scratch Hardness (MOHS)	7	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Complies		

PACKING INFORMATION - 6x36 *Please inquire with Customer Service for additional sizes*

SqFt. Per Carton		Pieces per Carton:	
SqFt per Pallet:		Pounds per Carton:	
Boxes per Pallet:		SqFt per Container:	
Pallets per Container:			

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".