

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Old Savannah

TECHNICAL CHARACTERISTICS

Available Formats:	4x4, 2x10		
Style Description:	Fume or Subway	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	4x4: 36, 2x10: 42
Thickness in mm:	4x4: 11.1mm, 2x10: 9.5mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Ceramic
Application:	Residential/Commercial	Color Body Unglazed:	
Recycled Content: Post or Pre Customer		Surface Type:	Glossy
Rectified:	Pressed	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	>10%	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	
Scratch Hardness (MOHS)	N/A	Breaking Strength:	
Frost Resistant:	No	Thermal Shock Resistance:	Resistant
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	GA-GLA		

PACKING INFORMATION - 2x10 *Please inquire with Customer Service for additional sizes*

SqFt. Per Carton	6.46	Pieces per Carton:	48
SqFt per Pallet:	620.16	Pounds per Carton:	
Boxes per Pallet:	96	SqFt per Container:	
Pallets per Container:	24		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".