## **NEW PRODUCT SERIES**

**Technical Information Spec-sheet** 





**SERIES NAME** 

**EMILIA** 

TECHNICAL CHARACTERISTICS					
Available Formats:	24x24				
Style Description:	Marble	Glaze Application Method:	Inkjet		
Visual Characteristics:		Number of Faces/Screens:	8		
Thickness in mm:	9.2 mm	Number of Punches/Molds:	1		
Modular Suitability:	Yes	Body Type:	Porcelain		
Application:	Commercial	Color Body Unglazed:	Off White		
Recycled Content: Post or Pre Customer	3%	Surface Type:	Matte/Flat		
Rectified:	Rectified	Recommended Grout Joint:	2mm		

PRODUCT TESTING INFORMATION						
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)						
Water Absorption:	<=0.5%	Static COF:				
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:				
Scratch Hardness (MOHS)	7	Breaking Strength:				
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A			
PEI/Abrasion Resistance:	4	Deep Abrasion Test	No			
		<175mm <sup>2</sup> :				
Chemical Resistance:	Pass					

PACKING INFORMATION - 2x10 Please inquire with Customer Service for additional sizes					
SqFt. Per Carton	15.29	Pieces per Carton:	4		
SqFt per Pallet:	550.44	Pounds per Carton:			
Boxes per Pallet:		SqFt per Container:			
Pallets per Container:	24				

## Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4% to 3/16% but no less than 1/8%.