

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

TAVOL

TECHNICAL CHARACTERISTICS

Available Formats:	12x48		
Style Description:	WOOD	Glaze Application Method:	Inkjet
Visual Characteristics:	WOOD	Number of Faces/Screens:	6
Thickness in mm:	9.6 mm (+/-) 5%	Number of Punches/Molds:	1
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	Off white
Recycled Content: Post or Pre Customer	3%	Surface Type:	Satin/Flat
Rectified:	Yes	Recommended Grout Joint:	2mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	Eb <= 0.5% Máx. ind. 0.6%	Static COF:	
Shade Variation (1, 2, 3, 4)	V3	Dynamic COF:	>0.60%
Scratch Hardness (MOHS)	5	Breaking Strength:	PASS
Frost Resistant:	Yes	Thermal Shock Resistance:	N/A
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	No
Chemical Resistance:	PASS		

PACKING INFORMATION - 6x36 Please inquire with Customer Service for additional sizes

SqFt. Per Carton	19.27	Pieces per Carton:	5
SqFt per Pallet:	693.72	Pounds per Carton:	
Boxes per Pallet:	36	SqFt per Container:	
Pallets per Container:	15		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".