

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

VULCANI

TECHNICAL CHARACTERISTICS

Available Formats:	6.5x15.75		
Style Description:	Interlock	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	15
Thickness in mm:	9 MM	Number of Punches/Molds:	1
Modular Suitability:		Body Type:	
Application:		Color Body Unglazed:	Neutral
Recycled Content: Post or Pre Customer		Surface Type:	Matte/textured
Rectified:	Pressed	Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	0.2	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	
Scratch Hardness (MOHS)	8	Breaking Strength:	932
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	5	Deep Abrasion Test <175mm ² :	Yes
Chemical Resistance:			

PACKING INFORMATION - *Please inquire with Customer Service for additional sizes*

SqFt. Per Carton	9.69	Pieces per Carton:	14
SqFt per Pallet:	629.85	Pounds per Carton:	
Boxes per Pallet:	65	SqFt per Container:	
Pallets per Container:	22		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".