

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

Native

TECHNICAL CHARACTERISTICS

Available Formats:	2" Hex, 2x4 Picket, 2" Penny		
Style Description:	Marble	Glaze Application Method:	
Thickness in mm:	6mm	Number of Faces/Screens:	
Application:	Residential Walls & Floors. Light Commercial Walls & Floors. Exterior Walls & Floors	Number of Punches/Molds:	
Rectified or Pressed:		Body Type:	Glass
Recycled Content: Post or Pre Customer	85%	Surface Type:	Flat
		Recommended Grout Joint:	

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	.03%-.05%	Chemical Resistance:	Class A
Shade Variation (1, 2, 3, 4)		Dynamic COF:	.59 Wet
Frost Resistant:	Yes	Breaking Strength:	1379 N
PEI/Abrasion Resistance:		Thermal Shock Resistance:	Pass

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacture. Use constitutes acceptance.