

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

NATIVE

TECHNICAL CHARACTERISTICS

Available Formats:	2 Hex, 2x4 Picket		
Style Description:	Digital Printing	Glaze Application Method:	
Visual Characteristics:	Marble	Number of Faces/Screens:	
Thickness in mm:	6 MM	Number of Punches/Molds:	
Modular Suitability:		Edge Type:	Molded
Application:	Residential Floor & Wall/Light Commercial/Exterior Wall/Exterior Floor/Shower/Steam Room/Fireplace- Hearth/Submerged/UV Rated	Surface Type:	Mesh
Recycled Content: Post or Pre Customer	85%	Mosaic Mounting Method	Mesh
Rectified:		Recommended Grout Joint:	6mm

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:		Static COF:	
Shade Variation (1, 2, 3, 4)		Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:		Thermal Shock Resistance:	
PEI/Abrasion Resistance:		Deep Abrasion Test <175mm ² :	
Chemical Resistance:			

PACKING INFORMATION - 2 Hex *Please inquire with Customer Service for additional sizes*

SqFt. Per Carton	12.8	Pieces per Carton:	13
SqFt per Pallet:	614.40	Pounds per Carton:	
Boxes per Pallet:	48	SqFt per Container:	
Pallets per Container:	31		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".