

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ARAVALI**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24 Matte		
Style Description:	Onyx	Glaze Application Method:	Inkjet
Visual Characteristics:	Onyx	Number of Faces/Screens:	24
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.70
Scratch Hardness (MOHS)		Breaking Strength:	2023.21 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Fully resistance
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ARAVALI**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24 Polished		
Style Description:	Onyx	Glaze Application Method:	Inkjet
Visual Characteristics:	Onyx	Number of Faces/Screens:	24
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	2023.21 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Fully resistance
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ARAVALI**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24 Matte		
Style Description:	Onyx	Glaze Application Method:	Inkjet
Visual Characteristics:	Onyx	Number of Faces/Screens:	12
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	0.70
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	2023.21 N
Frost Resistant:	Yes	Thermal Shock Resistance:	Fully Resistance
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**ARAVALI**

## TECHNICAL CHARACTERISTICS

Available Formats:	24x24 Polished		
Style Description:	Onyx	Glaze Application Method:	Inkjet
Visual Characteristics:	Onyx	Number of Faces/Screens:	12
Thickness in mm:	8.5 MM	Number of Punches/Molds:	1
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed Porcelain
Recycled Content: Post or Pre Customer	0%	Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	2mm- 3mm

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	
PEI/Abrasion Resistance:	3	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:			

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*