

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

BOSCO

TECHNICAL CHARACTERISTICS

Available Formats:	8x48		
Style Description:	Wood Plank	Glaze Application Method:	Inkjet
Visual Characteristics:	Wood Plank	Number of Faces/Screens:	10
Thickness in mm:	9 MM	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial	Color Body Unglazed:	Glazed
Recycled Content: Post or Pre Customer		Surface Type:	Matte
Rectified or Pressed	Rectified	Recommended Grout Joint:	Yes

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	<0.05%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	0.35
Scratch Hardness (MOHS)	Class >6	Breaking Strength:	<1300 N
Frost Resistant:	Yes	Thermal Shock Resistance:	YES
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	YES
Chemical Resistance:	Yes		

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.