

BossWood Technical Specifications

Description:	Luxury Engineered HDF Plank with Attached EVA Rubber Pad
Warranty:	Limited Lifetime Residential Wear Warranty 500 Hour Waterproof Spill Warranty on Top BossWood HDF Core - very water resistant 15 Year Limited Lt. Commercial Wear Warranty
Installation:	Unilin Click Angle Angle - Float with 6mil vapor barrier or Glue Down with Premium Pressure Sensitive Adhesive w vapor barrier all-in-one
Construction	Premium HDF Core Infused with Highest Rated European Nano-Glue 12mm (10 mm HDF core + 2mm pad) and AC4 Commercial Wear Layer Anti-Microbial Finish, Embossed-in-Register (EIR) Wood Grain Design, 4-sided V-Bevel

Size/Packing: BossWood - 9.5" x 72" x 12mm Planks 28.04 SF/Box, 6 Planks/Box, 53.83 Lbs/Box, 48 Boxes/Pallet, 1,345.92 SF/Pallet

TEST DATA

ASTM - E90-09 Airborne Sound Conduction: ASTM - E492-09 Impact Sound Conduction: ASTM - E2179 ASTM - F970 Static Load VOC Testing STC 53 (on 6" concrete slab w no drop ceiling) IIC 53 (on 6" concrete slab w no drop ceiling) Delta IIC 20 (on 6" concrete slab w no drop ceiling) 0.019 of an inch Green Guard Gold & Floor Score Certified



3500 SW 42nd Avenue Palm City, FL 34990 T: 1-800-340-TILE (8453) | F: 1-888-765-TILE (8453) | F: 1-772-223-0837 | E: info@iwttesoro.com www.iwttesoro.com