## **NEW PRODUCT SERIES**

**Technical Information Spec-sheet** 





SERIES NAME	EVER
-------------	------

TECHNICAL CHARACTERISTICS					
Available Formats:	12x24				
Style Description:	Marble Calacatta	Glaze Application Method:	Inkjet		
Visual Characteristics:		Number of Faces/Screens:	35		
Thickness in mm:	6.8	Number of Punches/Molds:			
Modular Suitability:	No	Body Type:	Porcelain		
Application:	Residential/Exterior	Color Body Unglazed:	Glazed		
Recycled Content:		Surface Type:	Matte/Flat		
Post or Pre Customer					
Rectified:	Pressed	Recommended Grout Joint:	MINIMUM 2 MM		

PRODUCT TESTING INFORMATION						
Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)						
Water Absorption:	≤ 0,5 %	Static COF:				
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42			
Scratch Hardness (MOHS)	5	Breaking Strength:				
Frost Resistant:	Yes	Thermal Shock Resistance:	Resists			
PEI/Abrasion Resistance:	4	Deep Abrasion Test	No			
		<175mm <sup>2</sup> :				
Chemical Resistance:	Α					

## Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".