

# NEW PRODUCT SERIES

Technical Information Spec-sheet



# International Wholesale Tile, LLC

SERIES NAME

**EVER**

## TECHNICAL CHARACTERISTICS

Available Formats:	12x24		
Style Description:	Marble Calacatta	Glaze Application Method:	Inkjet
Visual Characteristics:		Number of Faces/Screens:	35
Thickness in mm:	6.8	Number of Punches/Molds:	
Modular Suitability:	No	Body Type:	Porcelain
Application:	Residential/Exterior	Color Body Unglazed:	Glazed
Recycled Content: Post or Pre Customer		Surface Type:	Matte/Flat
Rectified:	Pressed	Recommended Grout Joint:	MINIMUM 2 MM

## PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	≤ 0,5 %	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	>0.42
Scratch Hardness (MOHS)	5	Breaking Strength:	
Frost Resistant:	Yes	Thermal Shock Resistance:	Resists
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	No
Chemical Resistance:	A		

*ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.*