

# NEW PRODUCT SERIES

Technical Information Spec-sheet



## International Wholesale Tile, LLC

SERIES NAME

**IBIZA**

### TECHNICAL CHARACTERISTICS

Available Formats:	24x24		
Style Description:	Calacatta	Glaze Application Method:	Inkjet
Visual Characteristics:	White Marble	Number of Faces/Screens:	8
Thickness in mm:	9 mm	Number of Punches/Molds:	
Modular Suitability:		Body Type:	Porcelain
Application:	Residential	Color Body Unglazed:	Grey
Recycled Content: Post or Pre Customer		Surface Type:	Glossy/Polished
Rectified:	Rectified	Recommended Grout Joint:	2 MM

### PRODUCT TESTING INFORMATION

*Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)*

Water Absorption:	<0.5%	Static COF:	
Shade Variation (1, 2, 3, 4)	V2	Dynamic COF:	
Scratch Hardness (MOHS)		Breaking Strength:	1600-2400 N
Frost Resistant:	Yes	Thermal Shock Resistance:	RESISTS ISO 10545-9
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm <sup>2</sup> :	
Chemical Resistance:	ISO 10545-13		

Note;

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".