

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

LARSEN

TECHNICAL CHARACTERISTICS

Available Formats:	12x24 & 24x24		
Style Description:	Marble	Glaze Application Method:	Inkjet
Visual Characteristics:	Marble	Number of Faces/Screens:	6
Thickness in mm:	8.5 mm	Number of Punches/Molds:	
Modular Suitability:	Yes	Body Type:	Porcelain
Application:	Residential/Commercial/Wall	Color Body Unglazed:	Glazed
Recycled Content: Post or Pre Customer	Green Building Certification, 100% Recycled Product	Surface Type:	Polished
Rectified:	Rectified	Recommended Grout Joint:	Spacer 3-4 MM

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

Water Absorption:	Avg $\leq 0.08\%$	Static COF:	
Shade Variation (1, 2, 3, 4)	V4	Dynamic COF:	Polished Tile-R9
Scratch Hardness (MOHS)	3-4 (12x24), 4-(24x24)	Breaking Strength:	Avg 1400N
Frost Resistant:	Yes	Thermal Shock Resistance:	10 cycles pass
PEI/Abrasion Resistance:	4	Deep Abrasion Test <175mm ² :	
Chemical Resistance:	Min. Class AA, Min Class- 1(Stain Resistance)		

Note:

Manufacturer does not recommend installing large format rectangular tile using a 50% staggered brick/running bond grout joint pattern. Joint locations can be random and should be positioned to be no less than 30% the length of the adjacent tile. Alternating joints so they are <30%, a straight-lay or herring bone patterns are acceptable and with grout joint sizes of 1/4" to 3/16" but no less than 1/8".