

NEW PRODUCT SERIES

Technical Information Spec-sheet



International Wholesale Tile, LLC

SERIES NAME

LUMINUS

TECHNICAL CHARACTERISTICS

| | | | |
|---|--------------------------------|---------------------------|----------------|
| Available Formats: | 12x24 | | |
| Style Description: | Contemporary White Marble | Glaze Application Method: | Inkjet |
| Visual Characteristics: | Marble with Gold/Cream Veining | Number of Faces/Screens: | 48 |
| Thickness in mm: | 8.25 MM | Number of Punches/Molds: | |
| Modular Suitability: | No | Body Type: | Porcelain |
| Application: | Residential/Commercial | Color Body Unglazed: | Only Glazed |
| Recycled Content: Post or Pre Customer | | Surface Type: | Matte/Polished |
| Rectified or Pressed | Rectified | Recommended Grout Joint: | |

PRODUCT TESTING INFORMATION

Please Note: All tests are completed per the US standards determined by the Tile Council of North America (TCNA)

| | | | |
|------------------------------|---------|---|-----------------|
| Water Absorption: | <0.5% | Static COF: | |
| Shade Variation (1, 2, 3, 4) | V2 | Dynamic COF: | .48 Wet |
| Scratch Hardness (MOHS) | | Breaking Strength: | 1897.8 N |
| Frost Resistant: | Yes | Thermal Shock Resistance: | Fully Resistant |
| PEI/Abrasion Resistance: | 3 | Deep Abrasion Test <175mm ² : | |
| Chemical Resistance: | Class 4 | | |

ANSI A108.02 Section 4.3.8.2 states that for running bond/joint brick patterns utilizing tiles (square or rectangle) where the side being offset is greater than 14" (nominal dimension), the running bond offset will be a maximum of 33% unless otherwise specified by the manufacturer. Use constitutes acceptance.